




















Gamma di incassi **orientabili** compatti nelle dimensioni. Grazie all'utilizzo di LED COB di altissima qualità (CRI 85 / a richiesta CRI 93) e ad ottiche estremamente efficienti le prestazioni illuminotecniche sono molto elevate e la distribuzione del flusso luminoso confortevole e "morbida". Un concetto di dissipazione avanzato consente di avere un apparecchio affidabile, molto compatto e leggero. A compact size range of adjustable downlights. Due to the use of high-quality LED COB (CRI 85 / CRI 93 on request) and efficient optics, lighting performance is very high and the distribution of the luminous flux is comfortable and smooth. An advanced dissipation concept allows a reliable, light and compact luminaire.

10W
250mA

						COOL WHITE	NATURAL WHITE	WARM WHITE	BLUE	RGB
ALU	 IP20			40°	1120A06T40_	-	N	W	-	-
ALU	 IP20			60°	1120A06T60_	-	N	W	-	-
ALU	 IP20			40°	1120A08T40_	-	N	W	-	-
ALU	 IP20			60°	1120A08T60_	-	N	W	-	-

ACCESSORI_TRASFOMATORI / ACCESSORIES_POWER SUPPLY UNITS



LLA-10-250

Alimentatore elettronico
Electronic power-supply unit
10W/250mA