




















Gamma di incassi trimless dalle dimensioni estremamente contenute ed elevate prestazioni illuminotecniche. Affidabili grazie alla eccellente dissipazione termica e alla scelta dei componenti. Disponibili con diverse temperature di colore e con diverse aperture di fascio. L'ottica arretrata rende il punto luce confortevole senza fenomeni di abbagliamento. A compact size and high performance range of trimless recessed downlights. Due to the excellent thermal dissipation and to the proper selection of components, these units are efficient and reliable. Available with different color temperatures and beam angles. A backward optics allows a comfortable no-glaring light.

10W  
250mA


						COOL WHITE	NATURAL WHITE	WARM WHITE	BLUE	RGB
ALU	 IP40			40°	1140A06T40_	-	N	W	-	-
ALU	 IP40			60°	1140A06T60_	-	N	W	-	-
ALU	 IP40			40°	1140A08T40_	-	N	W	-	-
ALU	 IP40			60°	1140A08T60_	-	N	W	-	-

ACCESSORI TRASFORMATORI / ACCESSORIES POWER SUPPLY UNITS



1140I000000

Controcassa per cartongesso  
Housing for plasterboard  
L = 110mm



LLA-10-250

Alimentatore elettronico  
Electronic power-supply unit  
10W/250mA